



### Main

Range of product	KNX
Product or component type	Roller shutter actuator
Operating mode	KNX bus system Manual
Bus type	KNX

### Complementary

18 mm pitches	4
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V AC 50...60 Hz
[In] rated current	10 A
Number of outputs	4
Load type	Motor : 434 W, 100 V AC Motor : 1000 W, 230 V AC Motor : 1043 W, 240 V AC
Local signalling	LED

### Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0809 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Product environmental profile	Available Available
-------------------------------	------------------------

---

Product end of life instructions	Available Available
----------------------------------	------------------------

---

**Contractual warranty**

---

Warranty period	18 months
-----------------	-----------

---

**Not classified OPS characteristics**

---

Market segment	Residential Small commercial
----------------	---------------------------------

---