



Main

Range of product	KNX
Product or component type	Blind switch actuator
Operating mode	KNX bus system Manual
Bus type	KNX

Complementary

18 mm pitches	12
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V AC 50...60 Hz
[In] rated current	10 A
Number of outputs	12
Load type	Parallel compensated fluorescent lamp : <= 434 VA, 100 V AC Parallel compensated fluorescent lamp : <= 1000 VA, 230 V AC Parallel compensated fluorescent lamp : <= 1043 VA, 240 V AC Motor : 434 W, 100 V AC Motor : 1000 W, 230 V AC Motor : 1043 W, 240 V AC Incandescent lamps : <= 869 W, 100 V AC Incandescent lamps : <= 2000 W, 230 V AC Incandescent lamps : <= 2086 W, 240 V AC Halogen lamps : <= 739 W, 100 V AC Halogen lamps : <= 1700 W, 230 V AC Halogen lamps : <= 1773 W, 240 V AC Capacitive : , 10 A, 105 µF, 100...240 V AC
Local signalling	LED

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0830 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------