



### Main

Range of product	KNX
Product or component type	Power supply
Network type	AC

### Complementary

Condition of use	Other device KNX device
Mounting support	DIN rail
Rated operational power in W	24 W
[Us] rated supply voltage	207...253 V AC 50/60 Hz
Output current	1 A
Output voltage	24 V
Connections - terminals	Screw terminals
Height	93 mm 66.5 mm
Width	87.5 mm
Depth	66.5 mm

### Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0647 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference contains SVHC above the threshold - Go to CaP for more details <a href="#">Go to CaP for more details</a>

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Available <a href="#">End of life manual</a>

---

**Contractual warranty**

---

Warranty period	18 months
-----------------	-----------

---

**Not classified OPS characteristics**

---

Market segment	Residential Small commercial
----------------	---------------------------------

---