



### Main

Range of product	KNX
Product or component type	Switch actuator
Operating mode	Manual
Bus type	KNX
Modular device additional info	Connectable with different phases
Number of contacts	2

### Complementary

Total number of 18 mm modules	2.5
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V
Network frequency	50...60 Hz
[In] rated current	16 A
Load type	Parallel compensated fluorescent lamp : <= 900 VA, 100 V AC Parallel compensated fluorescent lamp : <= 2000 VA, 230 V AC Parallel compensated fluorescent lamp : <= 2000 VA, 240 V AC Incandescent lamps : <= 1600 W, 100 V AC Incandescent lamps : <= 3600 W, 230 V AC Incandescent lamps : <= 3840 W, 240 V AC Halogen lamps : <= 2500 W, 230 V AC Halogen lamps : <= 1080 W, 100 V AC Halogen lamps : <= 2500 W, 240 V AC Capacitive : 16 A - 105 µF, 100...240 V AC

### Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

MTN6700-0002

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Available <a href="#">End of life manual</a>