



Main

Range of product	KNX
Product or component type	Switch actuator
Operating mode	Manual
Bus type	KNX
Modular device additional info	Connectable with different phases
Number of contacts	8

Complementary

Total number of 18 mm modules	8
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V
Network frequency	50...60 Hz
[In] rated current	16 A
Load type	Parallel compensated fluorescent lamp : <= 900 VA, 100 V AC Parallel compensated fluorescent lamp : <= 2000 VA, 230 V AC Parallel compensated fluorescent lamp : <= 2000 VA, 240 V AC Incandescent lamps : <= 1600 W, 100 V AC Incandescent lamps : <= 3600 W, 230 V AC Incandescent lamps : <= 3840 W, 240 V AC Halogen lamps : <= 2500 W, 230 V AC Halogen lamps : <= 1080 W, 100 V AC Halogen lamps : <= 2500 W, 240 V AC Capacitive : 16 A - 105 µF, 100...240 V AC

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

MTN6700-0008

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual