



### Main

|                           |                           |
|---------------------------|---------------------------|
| Range of product          | Unica                     |
| Range                     | Unica                     |
| Aesthetic name            | Unica Top - Unica Class   |
| Device application        | Control                   |
| Product or component type | Switch                    |
| Device presentation       | Mechanism                 |
| Switch function           | 1-pole 1-way              |
| Provided equipment        | Internal power connection |
| Colour tint               | Aluminium                 |

### Complementary

|                                       |   |
|---------------------------------------|---|
| Rated current                         | 10 AX, 250 V AC, 50/60 Hz   |
| Electrical durability                 | 10000 cycles  |
| Insulation resistance                 | > 5 MOhm @500 V   |
| Dielectric strength                   | 2000 V  |
| Minimum load breaking capacity        | 200 operations 1.25 In and 1.1 Un, cos phi: 0.3                       |
| Opening distance                      | > 3 mm  |
| Actuator                              | Rocker  |
| Number of modules                     | 2 modules   |
| Pilot light                           | Blue LED : 0.15 mA (temperature : 15 °C)                              |
| Connections - terminals               | Screw terminals   |
| Cable cross section                   | 0...2.5 mm <sup>2</sup> (rigid)<br>0...2.5 mm <sup>2</sup> (flexible) |
| Material                              | Mechanism cover : ABS (acrylonitrile butadiene-styrene)               |
| Fixing mode                           | Clip-in   |
| Width                                 | 45 mm   |
| Height                                | 45 mm   |
| Depth                                 | 34 mm   |
| Embedding depth                       | 22 mm   |
| Product weight                        | 0.0241 kg   |
| Ambient air temperature for operation | 25...35 °C  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                     |                                    |
|-------------------------------------|------------------------------------|
| Ambient air temperature for storage | 0...50 °C                          |
| Standards                           | EN 60669-1                         |
| Directives                          | 2014/35/EU - low voltage directive |
| Product certifications              | 14.10.01/5433                      |

## Environment

|                                 |  |
|---------------------------------|--|
| IP degree of protection         | IP20   |
| IK degree of protection         | IK01   |
| Environmental characteristic    | Oil<br>UV resistant<br>Window-cleaning fluid<br>Ammonia<br>Alcohol<br>Liquid soap<br>Bleach<br>Petrol<br>Acetone |
| Environmental health and issues | Halogen free   |