



Main

Range	Mureva Styl
Range of product	Mureva Styl
Product or component type	Rocker with indicator
Category	Rocker switch
Device presentation	Complete product
Colour tint	Grey (RAL 7016)

Complementary

Device mounting	Surface
Switch function	2-way
Actuator	Rocker
Rated current	10 AX
[Ue] rated operational voltage	250 V AC
Local signalling	LED blue
Current consumption	0.15 mA 250 V
Condition of use	Indoor/Outdoor
Material	ABS (acrylonitrile butadiene-styrene) Brass SEBS
Fixing mode	Screwless
Clamping connection capacity	1.5...2.5 mm ² rigid 1.5...2.5 mm ² flexible 1.5...2.5 mm ² stranded
Wire stripping length	13 mm
Cable entry	Easy valve access Ø 6...20 mm
Length	76 mm
Height	64 mm
Width	76 mm
Embedding depth	0 mm
Projecting depth	64 mm

MUR35024

Environment

Quality labels	NF CE EAC AENOR
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing ≥ 650 °C according to IEC 60695-2-1
Standards	EN 60669-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C