



Main

Range	Mureva Styl
Range of product	Mureva Styl
Product or component type	Push-button with pilot lamp
Category	Push-button with pilot lamp
Device presentation	Insert
Colour tint	Grey (RAL 7016)

Complementary

Device mounting	Surface Flush
Switch function	Push-button
Actuator	Push-button
Rated current	10 A
[Ue] rated operational voltage	250 V AC
Local signalling	LED blue
Current consumption	0.15 mA 250 V
Condition of use	Indoor/Outdoor
Material	SEBS ABS (acrylonitrile butadiene-styrene) Brass
Fixing mode	Screwless
Clamping connection capacity	1.5...2.5 mm ² rigid 1.5...2.5 mm ² flexible 1.5...2.5 mm ² stranded
Wire stripping length	13 mm
Length	71 mm
Height	40 mm
Width	71 mm
Embedding depth	10 mm
Projecting depth	60 mm

MUR35127

Environment

Quality labels	CE EAC NF AENOR
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing ≥ 650 °C according to IEC 60695-2-1
Standards	EN 60669-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C