



## Main

Range	Mureva Styl
Range of product	Mureva Styl
Product or component type	Power socket-outlet
Device presentation	Complete product
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	Schuko
Colour tint	Grey (RAL 7016)

## Complementary

Device mounting	Surface
Rated current	16 A
Number of power socket outlets	2
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/Outdoor
Material	Brass PP (polypropylene) PC (polycarbonate)
Fixing mode	Screwless
Clamping connection capacity	1...2.5 mm <sup>2</sup> rigid 1...2.5 mm <sup>2</sup> stranded 1...2.5 mm <sup>2</sup> flexible
Wire stripping length	13 mm
Cable entry	Easy valve access Ø 6...12 mm
Length	147 mm
Height	64 mm
Width	76 mm
Projecting depth	64 mm
Embedding depth	0 mm

## Environment

Quality labels	EAC
----------------	-----

# MUR36029

AENOR

IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing $\geq 650$ °C according to IEC 60695-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C