

Product data sheet
Characteristics

MUR36132

Mureva Styl - power socket-outlet with sideE -
16A 250V - 2P + E with shutters - grey



Main

Range	Mureva Styl
Range of product	Mureva Styl
Product or component type	Power socket-outlet
Device presentation	Complete product
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	Schuko
Colour tint	Grey (RAL 7016)

Complementary

Device mounting	Flush
Rated current	16 A
Number of power socket outlets	1
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/Outdoor
Material	Brass PP (polypropylene) PC (polycarbonate)
Fixing mode	Screwless
Clamping connection capacity	1...2.5 mm ² rigid 1...2.5 mm ² stranded 1...2.5 mm ² flexible
Wire stripping length	13 mm
Length	84 mm
Height	55 mm
Width	84 mm
Projecting depth	30 mm
Embedding depth	25 mm

Environment

Quality labels	EAC AENOR
----------------	--------------

MUR36132

IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing ≥ 650 °C according to IEC 60695-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C