



Main

| | |
|-----------------------------|----------------------|
| Range | Mureva Styl |
| Range of product | Mureva Styl |
| Product or component type | Power socket-outlet |
| Device presentation | Insert |
| Outlet poles configuration | 2P + E with shutters |
| Outlet standard description | Side earth |
| Outlet standard | Schuko |
| Colour tint | Grey (RAL 7016) |

Complementary

| | |
|--------------------------------|---|
| Device mounting | Surface Flush |
| Rated current | 16 A |
| Number of power socket outlets | 1 |
| [Ue] rated operational voltage | 250 V AC |
| Condition of use | Indoor/Outdoor |
| Material | Brass PP (polypropylene) PC (polycarbonate) |
| Fixing mode | Screwless |
| Clamping connection capacity | 1...2.5 mm ² rigid 1...2.5 mm ² stranded 1...2.5 mm ² flexible |
| Wire stripping length | 13 mm |
| Length | 71 mm |
| Height | 50 mm |
| Width | 71 mm |

Environment

| | |
|-------------------------|--------------|
| Quality labels | EAC AENOR |
| IP degree of protection | IP55 |
| IK degree of protection | IK08 |

| | |
|---------------------------------------|---|
| Flame retardance | Self-extinguishing ≥ 650 °C according to IEC 60695-2-1 |
| Ambient air temperature for operation | -5...40 °C |
| Ambient air temperature for storage | -25...55 °C |