



## Main

Range of product	Mureva Styl
Range	Mureva Styl
Product or component type	Rocker with indicator
Category	Rocker switch
Device presentation	Complete product
Colour tint	Grey (RAL 7016)

## Complementary

Device mounting	Flush
Switch function	2-way
Actuator	Rocker
Rated current	10 AX
[Ue] rated operational voltage	250 V AC
Local signalling	LED blue
Current consumption	0.15 mA 250 V
Condition of use	Indoor/Outdoor
Material	SEBS Brass ABS (acrylonitrile butadiene-styrene)
Fixing mode	Screwless
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> rigid 1.5...2.5 mm <sup>2</sup> flexible 1.5...2.5 mm <sup>2</sup> stranded
Wire stripping length	13 mm
Length	84 mm
Height	40 mm
Width	84 mm
Embedding depth	11 mm
Projecting depth	29 mm

## Environment

Quality labels	NF
----------------	----

# MUR36624

CE  
AENOR  
EAC

IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing $\geq 650$ °C according to IEC 60695-2-1
Standards	EN 60669-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C