



Main

Range of product	Mureva Styl
Range	Mureva Styl
Product or component type	Push-button with pilot lamp
Category	Push-button with pilot lamp
Device presentation	Complete product
Colour tint	Grey (RAL 7016)

Complementary

Device mounting	Flush
Switch function	Push-button
Actuator	Push-button
Rated current	10 A
[Ue] rated operational voltage	250 V AC
Local signalling	LED blue
Current consumption	0.15 mA 250 V
Condition of use	Indoor/Outdoor
Material	ABS (acrylonitrile butadiene-styrene) SEBS Brass
Fixing mode	Screwless
Clamping connection capacity	1.5...2.5 mm ² rigid 1.5...2.5 mm ² flexible 1.5...2.5 mm ² stranded
Wire stripping length	13 mm
Length	84 mm
Height	40 mm
Width	84 mm
Embedding depth	11 mm
Projecting depth	29 mm

Environment

Quality labels	CE
----------------	----

MUR36628

NF
AENOR
EAC

IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing ≥ 650 °C according to IEC 60695-2-1
Standards	EN 60669-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C