



Main

| | |
|-----------------------------|----------------------|
| Range of product | Mureva Styl |
| Range | Mureva Styl |
| Product or component type | Power socket-outlet |
| Device presentation | Complete product |
| Outlet poles configuration | 2P + E with shutters |
| Outlet standard description | Side earth |
| Outlet standard | Schuko |
| Colour tint | Grey (RAL 7016) |

Complementary

| | |
|--------------------------------|---|
| Device mounting | Surface |
| Rated current | 16 A |
| Number of power socket outlets | 1 |
| [Ue] rated operational voltage | 250 V AC |
| Condition of use | Indoor/Outdoor |
| Material | Brass PP (polypropylene) PC (polycarbonate) |
| Fixing mode | By screws |
| Cable entry | Easy valve access Ø 6...12 mm |
| Length | 76 mm |
| Height | 64 mm |
| Width | 76 mm |
| Projecting depth | 64 mm |
| Embedding depth | 0 mm |

Environment

| | |
|-------------------------|---|
| Quality labels | EAC AENOR |
| IP degree of protection | IP55 |
| IK degree of protection | IK08 |
| Flame retardance | Self-extinguishing ≥ 650 °C according to IEC 60695-2-1 |

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -5...40 °C |
| Ambient air temperature for storage | -25...55 °C |
