



### Main

Range	Mureva Styl
Range of product	Mureva Styl
Product or component type	Rocker switch
Category	Rocker switch
Device presentation	Complete product
Colour tint	White (RAL 9003)

### Complementary

Device mounting	Surface
Switch function	2-way
Actuator	Rocker
Rated current	10 AX
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/Outdoor
Material	ABS (acrylonitrile butadiene-styrene) Brass SEBS
Fixing mode	Screwless
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> rigid 1.5...2.5 mm <sup>2</sup> flexible 1.5...2.5 mm <sup>2</sup> stranded
Wire stripping length	13 mm
Cable entry	Easy valve access Ø 6...20 mm
Length	76 mm
Height	64 mm
Width	76 mm
Embedding depth	0 mm
Projecting depth	64 mm

### Environment

Quality labels	NF CE EAC
----------------	-----------------

MUR39021

AENOR

IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing $\geq 650$ °C according to IEC 60695-2-1
Standards	EN 60669-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C