



Main

| | |
|---------------------------|------------------------|
| Range | Mureva Styl |
| Range of product | Mureva Styl |
| Product or component type | Mechanical time switch |
| Device presentation | Complete product |
| Colour tint | White (RAL 9003) |
| Quantity per set | Set of 1 |

Complementary

| | |
|---------------------------|---|
| Device mounting | Surface |
| [Us] rated supply voltage | 230 V AC 50/60 Hz |
| Load interrupting current | 10 A (resistive, cosF=1) 6 A (inductive, cosF=0.6) |
| Time delay | 2...14 minutes 2 minutes |
| Control type | Turn switch |
| Condition of use | Indoor/Outdoor |
| Material | ABS (acrylonitrile butadiene-styrene) PP (polypropylene) SEBS |
| Fixing mode | By 2 screws |
| Cable entry | Easy valve access Ø 6...20 mm |
| Length | 76 mm |
| Height | 80 mm |
| Width | 76 mm |
| Depth | 80 mm |

Environment

| | |
|-------------------------|---|
| Quality labels | CE EAC |
| IP degree of protection | IP55 |
| IK degree of protection | IK08 |
| Flame retardance | Self-extinguishing ≥ 650 °C according to IEC 60695-2-1 |

| | |
|---------------------------------------|--------------|
| Standards | EN 60669-2-1 |
| Ambient air temperature for operation | -5...40 °C |
| Ambient air temperature for storage | -25...55 °C |