



## Main

Range	Mureva Styl
Range of product	Mureva Styl
Product or component type	Push-button with pilot lamp
Category	Push-button with pilot lamp
Device presentation	Insert
Colour tint	White (RAL 9003)

## Complementary

Device mounting	Surface Flush
Switch function	Push-button
Actuator	Push-button
Rated current	10 A
[Ue] rated operational voltage	250 V AC
Local signalling	LED blue
Current consumption	0.15 mA 250 V
Condition of use	Indoor/Outdoor
Material	SEBS ABS (acrylonitrile butadiene-styrene) Brass
Fixing mode	Screwless
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> rigid 1.5...2.5 mm <sup>2</sup> flexible 1.5...2.5 mm <sup>2</sup> stranded
Wire stripping length	13 mm
Length	71 mm
Height	40 mm
Width	71 mm
Embedding depth	10 mm
Projecting depth	60 mm

MUR39127

## Environment

Quality labels	AENOR CE EAC NF
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing $\geq 650$ °C according to IEC 60695-2-1
Standards	EN 60669-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C