



Main

| | |
|---------------------------|------------------|
| Range | Mureva Styl |
| Range of product | Mureva Styl |
| Product or component type | Rocker switch |
| Category | Rocker switch |
| Colour tint | White (RAL 9003) |

Complementary

| | |
|--------------------------------|---|
| Device mounting | Flush Surface |
| Switch function | 2-way |
| Actuator | Rocker |
| Rated current | 10 AX |
| [Ue] rated operational voltage | 250 V AC |
| Condition of use | Indoor/Outdoor |
| Material | PC (polycarbonate) ABS (acrylonitrile butadiene-styrene) |
| Length | 70 mm |
| Height | 14 mm |
| Width | 70 mm |
| Embedding depth | 10 mm |
| Projecting depth | 11 mm |

Environment

| | |
|---------------------------------------|---|
| Quality labels | AENOR NF |
| IP degree of protection | IP55 |
| IK degree of protection | IK08 |
| Flame retardance | Self-extinguishing ≥ 650 °C according to IEC 60695-2-1 |
| Standards | EN 60669-1 |
| Ambient air temperature for operation | -5...40 °C |
| Ambient air temperature for storage | -25...55 °C |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications