



Main

| | |
|---------------------------|------------------|
| Range | Mureva Styl |
| Range of product | Mureva Styl |
| Product or component type | Push-button |
| Category | Push-button |
| Device presentation | Insert |
| Colour tint | White (RAL 9003) |

Complementary

| | |
|--------------------------------|---|
| Device mounting | Surface |
| Switch function | Push-button |
| Actuator | Push-button |
| Rated current | 10 A |
| [Ue] rated operational voltage | 250 V AC |
| Condition of use | Indoor/Outdoor |
| Material | Brass ABS (acrylonitrile butadiene-styrene) SEBS |
| Fixing mode | Screwless |
| Clamping connection capacity | 1.5...2.5 mm ² rigid 1.5...2.5 mm ² flexible 1.5...2.5 mm ² stranded |
| Wire stripping length | 13 mm |
| Cable entry | Easy valve access Ø 6...20 mm |
| Length | 76 mm |
| Height | 64 mm |
| Width | 76 mm |
| Embedding depth | 0 mm |
| Projecting depth | 64 mm |

Environment

| | |
|----------------|-------------------|
| Quality labels | AENOR CE NF |
|----------------|-------------------|

MUR39626

EAC

| | |
|---------------------------------------|---|
| IP degree of protection | IP55 |
| IK degree of protection | IK08 |
| Flame retardance | Self-extinguishing ≥ 650 °C according to IEC 60695-2-1 |
| Standards | EN 60669-1 |
| Ambient air temperature for operation | -5...40 °C |
| Ambient air temperature for storage | -25...55 °C |