



## Main

Range of product	Mureva Styl
Range	Mureva Styl
Product or component type	Rocker switch
Category	Rocker switch
Device presentation	Complete product
Provided equipment	Supplied with claws
Colour tint	White (RAL 9003)

## Complementary

Device mounting	Flush
Switch function	2-way
Actuator	Rocker
Rated current	10 AX
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/Outdoor
Material	Brass ABS (acrylonitrile butadiene-styrene) SEBS
Fixing mode	Screwless
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> rigid 1.5...2.5 mm <sup>2</sup> flexible 1.5...2.5 mm <sup>2</sup> stranded
Wire stripping length	13 mm
Length	84 mm
Height	56 mm
Width	84 mm
Embedding depth	27 mm
Projecting depth	29 mm

## Environment

Quality labels	CE NF AENOR
----------------	-------------------

# MUR39721

EAC

IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing $\geq 650$ °C according to IEC 60695-2-1
Standards	EN 60669-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C