



### Main

|                             |                      |
|-----------------------------|----------------------|
| Range                       | Mureva Styl          |
| Range of product            | Mureva Styl          |
| Product or component type   | Power socket-outlet  |
| Device presentation         | Complete product     |
| Outlet poles configuration  | 2P + E with shutters |
| Outlet standard description | Side earth           |
| Colour tint                 | Grey (RAL 7016)      |

### Complementary

|                                |   |
|--------------------------------|---|
| Device mounting                | Surface   |
| Rated current                  | 16 A  |
| Number of power socket outlets | 2   |
| [Ue] rated operational voltage | 250 V AC  |
| Condition of use               | Indoor/Outdoor                                    |
| Material                       | PP (polypropylene)<br>PC (polycarbonate)<br>Brass |
| Fixing mode                    | By screws   |
| Cable entry                    | Easy valve access Ø 6...12 mm                     |
| Length                         | 147 mm  |
| Height                         | 64 mm   |
| Width                          | 76 mm   |
| Projecting depth               | 64 mm   |
| Embedding depth                | 0 mm  |

### Environment

|                         |   |
|-------------------------|---|
| Quality labels          | AENOR<br>CE<br>EAC  |
| IP degree of protection | IP55  |
| IK degree of protection | IK08  |
| Flame retardance        | Self-extinguishing $\geq 650$ °C according to IEC 60695-2-1 |

---

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -5...40 °C  |
| Ambient air temperature for storage   | -25...55 °C |

---