



### Main

|                           |               |
|---------------------------|---------------|
| Range of product          | Mureva Styl   |
| Range                     | Mureva Styl   |
| Product or component type | Rocker switch |
| Category                  | Rocker switch |
| Device presentation       | Insert        |
| Colour tint               | Grey          |

### Complementary

|                                |  |
|--------------------------------|--|
| Device mounting                | Surface  |
| Switch function                | Double 2-way   |
| Actuator                       | Rocker   |
| Rated current                  | 10 AX  |
| [Ue] rated operational voltage | 250 V AC   |
| Condition of use               | Indoor/Outdoor   |
| Material                       | Brass<br>ABS (acrylonitrile butadiene-styrene)<br>SEBS |
| Cable entry                    | Easy valve access Ø 6...20 mm                          |
| Length                         | 76 mm  |
| Height                         | 64 mm  |
| Width                          | 76 mm  |
| Embedding depth                | 0 mm   |
| Projecting depth               | 64 mm  |

### Environment

|                         |   |
|-------------------------|---|
| Quality labels          | NF<br>AENOR<br>EAC<br>CE                                    |
| IP degree of protection | IP55  |
| IK degree of protection | IK08  |
| Flame retardance        | Self-extinguishing $\geq 650$ °C according to IEC 60695-2-1 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |             |
|---------------------------------------|-------------|
| Standards                             | EN 60669-1  |
| Ambient air temperature for operation | -5...40 °C  |
| Ambient air temperature for storage   | -25...55 °C |