



Main

| | |
|-----------------------------|-------------------------------|
| Range of product | EasyPact MVS |
| Range | EasyPact |
| Product name | MVS08N |
| Device short name | MVS08N |
| Product or component type | Circuit breaker |
| Device application | Distribution |
| Poles description | 3P |
| Protected poles description | 3P 3d |
| Network type | AC |
| Breaking capacity code | N |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category B |
| Trip unit name | ETV5S |
| Trip unit technology | Electronic |
| Trip unit rating | 800 A |

Complementary

| | |
|--|--|
| Network frequency | 50/60 Hz |
| Control type | Manually operated |
| Mounting mode | Drawout |
| Mounting support | Base plate Rail |
| Connection position | Horizontal Vertical |
| Location of connection | Rear |
| [In] rated current | 800 A (40 °C) |
| [Ui] rated insulation voltage | 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 12 kV conforming to IEC 60947-2 |

| | |
|--|--|
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Circuit breaker CT rating | 800 A |
| Breaking capacity | 50 kA (Icu) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | 50 kA (Ics) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability | 20000 cycles (with maintenance) conforming to IEC 60947-2 10000 cycles (without maintenance) conforming to IEC 60947-2 |
| Electrical durability | 6000 cycles (without maintenance), category B at 440 V AC 50/60 Hz, conforming to IEC 60947-2 4000 cycles (without maintenance), category B at 690 V AC 50/60 Hz, conforming to IEC 60947-2 |
| Connection pitch | 115 mm (without spreader) |
| Contact position indicator | Yes |
| [Icm] rated short-circuit making capacity | 105 kA (Icm) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Icw] rated short-time withstand current | 50 kA (1 s) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2 42 kA (1 s) at 690 V AC 50/60 Hz conforming to IEC 60947-2 25 kA (3 s) at 440/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Trip unit protection functions | LSI |
| Protection type | Overload protection (long time) Short time short-circuit protection Instantaneous short-circuit protection |
| Fault indication | Internal fault Overload Short-circuit |
| Long time pick-up adjustment type Ir | Adjustable 9 settings |
| Long time pick-up adjustment range | 0.4...1 x In |
| Long time delay adjustment type | Adjustable 9 settings |
| [Tr] long-time delay adjustment range | 0.5...24 s (6 x Ir) |
| Short-time pick-up adjustment type I _{sd} | Adjustable 9 settings |
| [I _{sd}] short-time pick-up adjustment range | 1.5...10 x Ir |
| Short-time delay adjustment type | Adjustable 5 settings |
| [T _{sd}] short-time delay adjustment range | 100...400 ms |
| Instantaneous pick-up adjustment type I _{li} | Adjustable 9 settings |
| Instantaneous pick-up adjustment range | 2...15 x In Off |
| Zone selective interlocking ZSI | With |
| Display type | Digital display |
| Type of measurement | Voltage |
| Current sensor rating range | 400/2000 A |
| Maximum breaking time | 25 ms |
| Closing response time | < 70 ms |
| Height | 439 mm |
| Width | 441 mm |
| Depth | 395 mm |
| Product weight | 70 kg |
| Compatibility code | MVS08N |

Environment

| | |
|---------------------------------------|-----------------------------|
| Standards | IEC 60947-2 |
| Product certifications | CCC CCS IEC GOST |
| IP degree of protection | IP40 |
| Pollution degree | 4 conforming to IEC 60664-1 |
| Ambient air temperature for operation | -5...70 °C |

| | |
|-------------------------------------|---|
| Ambient air temperature for storage | -40...85 °C (without control unit) -25...85 °C (with control unit) |
|-------------------------------------|---|

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1440 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Available End of life manual |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

MVS08N3MW5V