



Main

| | |
|-----------------------------|-------------------------------|
| Range of product | EasyPact MVS |
| Range | EasyPact |
| Product name | MVS10H |
| Device short name | MVS10H |
| Product or component type | Circuit breaker |
| Device application | Distribution |
| Poles description | 3P |
| Protected poles description | 3P 3d |
| Network type | AC |
| Breaking capacity code | H |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category B |
| Trip unit name | ET6G |
| Trip unit technology | Electronic |
| Trip unit rating | 1000 A |

Complementary

| | |
|--|--|
| Network frequency | 50/60 Hz |
| Control type | Electrically operated |
| Mounting mode | Fixed |
| Mounting support | Base plate Rail |
| Connection position | Vertical Horizontal |
| Location of connection | Rear |
| [In] rated current | 1000 A (40 °C) |
| [Ui] rated insulation voltage | 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 12 kV conforming to IEC 60947-2 |

| | |
|--|--|
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Circuit breaker CT rating | 1000 A |
| Breaking capacity | 65 kA (Icu) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | 65 kA (Ics) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2 50 kA (Ics) at 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability | 20000 cycles (with maintenance) conforming to IEC 60947-2 10000 cycles (without maintenance) conforming to IEC 60947-2 |
| Electrical durability | 6000 cycles (without maintenance), category B at 440 V AC 50/60 Hz, conforming to IEC 60947-2 4000 cycles (without maintenance), category B at 690 V AC 50/60 Hz, conforming to IEC 60947-2 |
| Connection pitch | 115 mm (without spreader) |
| Contact position indicator | Yes |
| [Icm] rated short-circuit making capacity | 143 kA (Icm) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Icw] rated short-time withstand current | 65 kA (1 s) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2 50 kA (1 s) at 690 V AC 50/60 Hz conforming to IEC 60947-2 36 kA (3 s) at 440/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Trip unit protection functions | LSIG |
| Protection type | Earth fault Short time short-circuit protection Overload protection (long time) Instantaneous short-circuit protection |
| Fault indication | Short-circuit Overload Internal fault Earth fault |
| Long time pick-up adjustment type Ir | Adjustable 9 settings |
| Long time pick-up adjustment range | 0.4...1 x In |
| Long time delay adjustment type | Adjustable 9 settings |
| [Tr] long-time delay adjustment range | 0.5...24 s (6 x Ir) |
| Short-time pick-up adjustment type I _{sd} | Adjustable 9 settings |
| [I _{sd}] short-time pick-up adjustment range | 1.5...10 x Ir |
| Short-time delay adjustment type | Adjustable 5 settings |
| [T _{sd}] short-time delay adjustment range | 100...400 ms |
| Instantaneous pick-up adjustment type I _{li} | Adjustable 9 settings |
| Instantaneous pick-up adjustment range | Off 2...15 x In |
| Ground-fault pick-up adjustment type | Adjustable 9 settings |
| Ground-fault time delay adjustment type -tg | Adjustable 5 settings |
| [T _g] ground-fault time delay adjustment range | 100...400 ms |
| [I _g] ground-fault pick-up adjustment range | 0.2...1 x In |
| Zone selective interlocking ZSI | With |
| Current sensor rating range | 400/2000 A |
| Maximum breaking time | 25 ms |
| Closing response time | < 70 ms |
| Height | 352 mm |
| Width | 422 mm |
| Depth | 297 mm |
| Product weight | 40 kg |
| Compatibility code | MVS10H |

Environment

| | |
|-----------|-------------|
| Standards | IEC 60947-2 |
|-----------|-------------|

| | |
|---------------------------------------|---|
| Product certifications | GOST IEC CCC CCS |
| IP degree of protection | IP40 |
| Pollution degree | 4 conforming to IEC 60664-1 |
| Ambient air temperature for operation | -5...70 °C |
| Ambient air temperature for storage | -40...85 °C (without control unit) -25...85 °C (with control unit) |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1440 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

MVS10H3NF6L