



### Main

|                            |  |
|----------------------------|--|
| Range of product           | OsiSense XC  |
| Series name                | Special format   |
| Product or component type  | Limit switch head  |
| Device short name          | ZC2J   |
| Head type                  | Plunger head   |
| Product compatibility      | XC2J   |
| Associated body            | ZC2JD1<br>ZC2JC18<br>ZC2JC1<br>ZC2JC2<br>ZC2JC28<br>ZC2JD2 |
| Movement of operating head | Linear   |
| Type of operator           | End plunger spring return metal                            |
| Type of approach           | Vertical approach 1 direction                              |

### Complementary

|                     |               |
|---------------------|---------------|
| Switch actuation    | On end        |
| Positive opening    | Without       |
| Product weight      | 0.195 kg      |
| Head material       | Metal         |
| Device presentation | Basic element |
| Compatibility code  | ZC2J          |

### Environment

|                                       |                      |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C          |
| Ambient air temperature for storage   | -40...70 °C          |
| Environmental characteristic          | Standard environment |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

**Offer Sustainability**

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0953 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product end of life instructions | Need no specific recycling operations   |

**Contractual warranty**

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|