

# ZCE6A

limit switch head ZCE - side cat's whisker with silicone boot



## Main

|                           |   |
|---------------------------|---|
| Range of product          | OsiSense XC   |
| Series name               | Standard format   |
| Product or component type | Limit switch head   |
| Device short name         | ZCE   |
| Head type                 | Multi-directional head  |
| Product compatibility     | XCKD<br>XCKP<br>XCKT<br>XCMD  |
| Associated body           | ZCD21<br>ZCD21M12<br>ZCD25<br>ZCD26<br>ZCD27<br>ZCD28<br>ZCD29<br>ZCD29M12<br>ZCD31<br>ZCD35<br>ZCD37<br>ZCD39<br>ZCMD21C12<br>ZCMD21L08R12<br>ZCMD21L08U78<br>ZCMD21L1<br>ZCMD21L2<br>ZCMD21L5<br>ZCMD21M12<br>ZCMD25L1<br>ZCMD25L2<br>ZCMD25L5<br>ZCMD29C12<br>ZCMD29L1<br>ZCMD29L2<br>ZCMD29L5<br>ZCMD37L1<br>ZCMD37L2 |

ZCE6A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCMD37L5  
 ZCMD39L1  
 ZCMD39L2  
 ZCMD39L5  
 ZCMD41L1  
 ZCMD41L2  
 ZCMD41L5  
 ZCMD61C12  
 ZCMD61M12  
 ZCMD69C12  
 ZCMD81L1  
 ZCMD81L2  
 ZCMD81L5  
 ZCP21  
 ZCP21M12  
 ZCP25  
 ZCP26  
 ZCP27  
 ZCP28  
 ZCP29  
 ZCP29M12  
 ZCP31  
 ZCP35  
 ZCP37  
 ZCP39  
 ZCT21G11  
 ZCT21N12  
 ZCT21P16  
 ZCT25G11  
 ZCT25N12  
 ZCT25P16  
 ZCT26G11  
 ZCT26N12  
 ZCT26P16  
 ZCT27G11  
 ZCT27N12  
 ZCT27P16  
 ZCT28G11  
 ZCT28N12  
 ZCT28P16

|                            |   |
|----------------------------|---|
| Movement of operating head | Multi-directional                                     |
| Type of operator           | Side cat's whisker spring return (with silicone boot) |
| Type of approach           | Multi-directional approach                            |

### Complementary

|                    |                    |
|--------------------|--------------------|
| Switch actuation   | By any moving part |
| Positive opening   | Without            |
| Compatibility code | ZCE                |

### Environment

|                                       |                      |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C          |
| Ambient air temperature for storage   | -40...70 °C          |
| Environmental characteristic          | Standard environment |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0851 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

# ZCE6A