Product data sheet Characteristics

ZCEG1

limit switch head ZCE - M16 booted nitrile end plunger





Main

Main	
Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	M16 plunger head
Product compatibility	XCKP XCMD XCKD XCKT
Associated body	ZCMD29C12 ZCMD29C12 ZCMD21L5 ZCMD81L1 ZCMD41L1 ZCMD41L5 ZCMD81L5 ZCMD21L1 ZCMD39L2 ZCMD39L5 ZCMD21C12 ZCMD21C12 ZCMD21M12 ZCMD21M12 ZCMD21M12 ZCMD25L5 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD29L5 ZCMD39L1 ZCMD39L1 ZCMD39L1 ZCMD37L1 ZCMD37L1 ZCMD37L1 ZCMD69C12 ZCMD69C12 ZCMD69C12 ZCMD29L2 ZCMD29L2 ZCMD29L1 ZCMD25L1 ZCMD25L1 ZCMD25L1 ZCMD25L1 ZCMD25L1

ZCMD37L2

Movement of operating head	Linear
Type of operator	End plunger spring return metal (with nitrile boot)
Type of approach	Vertical approach 1 direction

Complementary

Positive opening	With
Device presentation	Basic element
Compatibility code	ZCE

Environment

Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C
Environmental characteristic	Standard environment

Offer Sustainability

ompliant - since 0851 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
Schneider Electric declaration of conformity
eference not containing SVHC above the threshold
eference not containing SVHC above the threshold
eed no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------