



ZCK D15

Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKM XCKL
Associated body	ZCKMD37H29 ZCKL8H7 ZCKLD31H7 ZCKL6H7 ZCKMD39H7 ZCKM7 ZCKL7 ZCKLD35 ZCKM1 ZCKM9 ZCKMD35H29 ZCKL7H7 ZCKLD37H7 ZCKMD31H29 ZCKM7H29 ZCKL5 ZCKM5 ZCKM8H7 ZCKL6 ZCKLD31 ZCKMD31H7 ZCKL5H7 ZCKM6 ZCKMD31 ZCKMD39H29 ZCKMD35H7 ZCKM7H7 ZCKM8 ZCKMD37H7 ZCKM5H7 ZCKLD39 ZCKM6H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKMD39
 ZCKMD37
 ZCKM8H29
 ZCKLD39H7
 ZCKM1H7
 ZCKM1H29
 ZCKMD35
 ZCKM6H7
 ZCKL8
 ZCKL1H7
 ZCKM5H29
 ZCKLD35H7
 ZCKLD37
 ZCKL1
 ZCKM9H29

Movement of operating head	Rotary
Type of operator	Roller lever spring return thermoplastic
Type of approach	Lateral approach 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal
Device presentation	Basic element
Compatibility code	ZCKD

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0951 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------