



Main

| | |
|----------------------------|---|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch head |
| Device short name | ZCKD |
| Head type | Rotary head |
| Product compatibility | XCKS |
| Associated body | ZCKS5 ZCKSD35H29 ZCKSD37 ZCKS8 ZCKS2 ZCKSD39H29 ZCKS2H29 ZCKS7H29 ZCKS9 ZCKS9H29 ZCKS6 ZCKS7 ZCKSD35 ZCKSD37H29 ZCKS8H29 ZCKSD31H29 ZCKSD31 ZCKSD39 ZCKS1 ZCKS1H29 ZCKS6H29 ZCKS5H29 |
| Movement of operating head | Rotary |
| Type of operator | Rod lever spring return metal (square rod 3 mm, L = 125 mm) |
| Type of approach | Lateral approach 2 directions |

Complementary

| | |
|---------------------|--------------------|
| Switch actuation | By any moving part |
| Positive opening | Without |
| Head material | Plastic |
| Device presentation | Basic element |
| Compatibility code | ZCKD |

Environment

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Offer Sustainability

| | |
|----------------------------------|--|
| RoHS (date code: YYWW) | Will not be compliant Will not be compliant |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|