



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJD37 ZCKJ4H29 ZCKJ8H7 ZCKJD39H29 ZCKJ9H7 ZCKJ41H7 ZCKJ11 ZCKJ6 ZCKJ6H29 ZCKJD39H7 ZCKJD31H7 ZCKJ2H29 ZCKJ21H29 ZCKJD37H29 ZCKJD37H7 ZCKJD35 ZCKJD31 ZCKJ1H7 ZCKJ21H7 ZCKJ2H7 ZCKJ7H29 ZCKJ5H29 ZCKJ4 ZCKJ5H7 ZCKJ7H7 ZCKJ41 ZCKJD35H7 ZCKJD35H29 ZCKJ7 ZCKJ1 ZCKJ5

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ9
 ZCKJ2
 ZCKJ4H7
 ZCKJ11H29
 ZCKJ11H7
 ZCKJD31H29
 ZCKJ9H29
 ZCKJ8
 ZCKJ1H29
 ZCKJ8H29
 ZCKJ6H7
 ZCKJD39
 ZCKJ41H29
 ZCKJ21

Movement of operating head	Linear
Type of operator	Roller lever plunger spring return thermoplastic
Type of approach	Lateral approach 1 direction

Complementary

Switch actuation	By 30° cam
Positive opening	With
Product weight	0.185 kg
Head material	Metal
Device presentation	Basic element
Compatibility code	ZCKE

Environment

Ambient air temperature for operation	10...120 °C
Ambient air temperature for storage	10...120 °C
Environmental characteristic	High temperature

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1037 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------