Product data sheet Characteristics

ZCKE216

limit switch head ZCKE - thermoplastic roller lever plunger - -40 $^{\circ}\text{C}$





Main

Main	
Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ5 ZCKJ9 ZCKJD311 ZCKJD311 ZCKJ2H7 ZCKJ4H7 ZCKJ6H7 ZCKJ6H7 ZCKJ8 ZCKJ4H29 ZCKJB39H7 ZCKJB129 ZCKJD39H7 ZCKJ2H29 ZCKJD35 ZCKJ7 ZCKJBH7 ZCKJ11 ZCKJ8H7 ZCKJ9H7 ZCKJ9H7 ZCKJ11 ZCKJ11 ZCKJ11 ZCKJ11H7 ZCKJ11 ZCKJ11H29 ZCKJ11H2

ZCKJ21 ZCKJ7H29 ZCKJ41H29 ZCKJ7H7 ZCKJ11H29 ZCKJ5H7 ZCKJD37 ZCKJD37H29 ZCKJ1H7 ZCKJD39H29 ZCKJD31H7 ZCKJD11 ZCKJ11 ZCKJ4 ZCKJ21H29

Movement of operating head	Linear
Type of operator	Roller lever plunger spring return thermoplastic
Type of approach	Lateral approach 1 direction

Complementary

Switch actuation	By 30° cam	
Positive opening	With	
Product weight	0.185 kg	
Head material	Metal	
Device presentation	Basic element	
Compatibility code	ZCKE	

Environment

Ambient air temperature for operation	-4070 °C
Ambient air temperature for storage	-4070 °C
Environmental characteristic	Low temperature

Offer Sustainability

Green Premium product
Compliant - since 1037 - Schneider Electric declaration of conformity
Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold
Reference not containing SVHC above the threshold
Need no specific recycling operations

Contractual warranty

|--|