



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ5 ZCKJ2H7 ZCKJ11H29 ZCKJ6 ZCKJ11H7 ZCKJ8H29 ZCKJ7 ZCKJD35H7 ZCKJD31H29 ZCKJ1H7 ZCKJD37 ZCKJ4H29 ZCKJ9H29 ZCKJ7H7 ZCKJ5H29 ZCKJD35 ZCKJ7H29 ZCKJ2H29 ZCKJD39 ZCKJ21H29 ZCKJ2 ZCKJ6H29 ZCKJ9 ZCKJ4H7 ZCKJD35H29 ZCKJ4 ZCKJ8H7 ZCKJ1H29 ZCKJD31H7 ZCKJ41 ZCKJ5H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ41H29
 ZCKJ8
 ZCKJD39H7
 ZCKJ9H7
 ZCKJ6H7
 ZCKJD37H7
 ZCKJ21H7
 ZCKJ21
 ZCKJ1
 ZCKJD39H29
 ZCKJD37H29
 ZCKJD31
 ZCKJ41H7
 ZCKJ11

Movement of operating head	Linear
Type of operator	Roller plunger spring return metal (with protective boot)
Type of approach	Lateral approach 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal
Device presentation	Basic element
Compatibility code	ZCKE

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1014 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------