



## Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ7 ZCKJD37H29 ZCKJ9 ZCKJ6H7 ZCKJD39 ZCKJ21H29 ZCKJ2H29 ZCKJ8H7 ZCKJ21H7 ZCKJ8 ZCKJ11H29 ZCKJ6 ZCKJ11 ZCKJ5H7 ZCKJ2 ZCKJ1 ZCKJD37 ZCKJD35 ZCKJ6H29 ZCKJ7H7 ZCKJD31H29 ZCKJD39H7 ZCKJD37H7 ZCKJD31 ZCKJD39H29 ZCKJ8H29 ZCKJ21 ZCKJ1H7 ZCKJD35H7 ZCKJ9H29 ZCKJ7H29 ZCKJ2H7 ZCKJ9H7 ZCKJD35H29 ZCKJ5H29 ZCKJ1H29 ZCKJD31H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCKJ11H7  
ZCKJ5

Movement of operating head	Linear
Type of operator	Side plunger spring return metal
Type of approach	Lateral approach 1 direction

### Complementary

Switch actuation	On end
Positive opening	With
Product weight	0.2 kg
Head material	Metal
Device presentation	Basic element
Compatibility code	ZCKE

### Environment

Ambient air temperature for operation	10...120 °C
Ambient air temperature for storage	10...120 °C
Environmental characteristic	High temperature

### Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------