



## Main

|                           |   |
|---------------------------|---|
| Range of product          | OsiSense XC   |
| Series name               | Standard format   |
| Product or component type | Limit switch head   |
| Device short name         | ZCKE  |
| Head type                 | Plunger head  |
| Product compatibility     | XCKJ  |
| Associated body           | ZCKJD39<br>ZCKJD31H7<br>ZCKJ1<br>ZCKJD31H29<br>ZCKJ5H7<br>ZCKJ9H7<br>ZCKJ21<br>ZCKJD37H29<br>ZCKJ11H7<br>ZCKJ6H7<br>ZCKJ9H29<br>ZCKJD37<br>ZCKJD35H29<br>ZCKJ1H29<br>ZCKJD31<br>ZCKJ7<br>ZCKJ8H7<br>ZCKJ5<br>ZCKJ6H29<br>ZCKJ2H29<br>ZCKJ9<br>ZCKJ7H7<br>ZCKJ6<br>ZCKJ21H7<br>ZCKJ11<br>ZCKJ1H7<br>ZCKJD39H29<br>ZCKJ11H29<br>ZCKJD37H7<br>ZCKJ21H29<br>ZCKJ2 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ8  
ZCKJ2H7  
ZCKJD39H7  
ZCKJ5H29  
ZCKJD35  
ZCKJD35H7  
ZCKJ8H29  
ZCKJ7H29

|                            |                                  |
|----------------------------|----------------------------------|
| Movement of operating head | Linear                           |
| Type of operator           | Side plunger spring return metal |
| Type of approach           | Lateral approach 1 direction     |

### Complementary

|                     |               |
|---------------------|---------------|
| Switch actuation    | On end        |
| Positive opening    | With          |
| Product weight      | 0.2 kg        |
| Head material       | Metal         |
| Device presentation | Basic element |
| Compatibility code  | ZCKE          |

### Environment

|                                       |                 |
|---------------------------------------|-----------------|
| Ambient air temperature for operation | -40...70 °C     |
| Ambient air temperature for storage   | -40...70 °C     |
| Environmental characteristic          | Low temperature |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1014 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product end of life instructions | Need no specific recycling operations   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|