



ZCK E66

Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ7H7 ZCKJ4 ZCKJ1H7 ZCKJ5H7 ZCKJ1 ZCKJD37 ZCKJ5H29 ZCKJ2 ZCKJ6 ZCKJD31H29 ZCKJD31 ZCKJ8 ZCKJ2H7 ZCKJ8H7 ZCKJ21H7 ZCKJ7 ZCKJ41H29 ZCKJ6H7 ZCKJD35H29 ZCKJD39 ZCKJ1H29 ZCKJ2H29 ZCKJ11H7 ZCKJ9 ZCKJ21H29 ZCKJ21 ZCKJ8H29 ZCKJD39H29 ZCKJ41H7 ZCKJ5 ZCKJ11H29 ZCKJD35H7 ZCKJD39H7 ZCKJD31H7 ZCKJ4H29 ZCKJD37H7 ZCKJ41

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCKJ7H29
ZCKJ6H29
ZCKJ9H7
ZCKJD37H29
ZCKJD35
ZCKJ9H29
ZCKJ4H7
ZCKJ11

Movement of operating head	Linear
Type of operator	End plunger spring return metal (ball bearing mounted)
Type of approach	Multi-directional approach

Complementary

Switch actuation	By 30° cam
Positive opening	With
Product weight	0.15 kg
Head material	Metal
Device presentation	Basic element
Compatibility code	ZCKE

Environment

Ambient air temperature for operation	10...120 °C
Ambient air temperature for storage	10...120 °C
Environmental characteristic	High temperature

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------