



Main

| | |
|-------------------------------|--|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch body |
| Device short name | ZCKJ |
| Body type | Fixed |
| Product compatibility | XCKJ |
| Associated head | ZCKE62 ZCKE65 ZCKE05 ZCKE63 ZCKE08 ZCKE619 ZCKE23 ZCKE06 ZCKE21 ZCKE61 ZCKE67 ZCKE66 ZCKE64 ZCKE629 |
| Body material | Metal |
| Cable entry | 1 entry tapped for Pg 13.5 cable gland |
| Number of poles | 2 |
| Contacts type and composition | 2 NC |
| Contact operation | Slow-break, simultaneous |
| Number of steps | 1 1 position |
| Contacts material | Silver plated contacts |

Complementary

| | |
|-----------------------|---|
| Local display | Without |
| Electrical connection | Screw-clamp terminals, clamping capacity: 1 x 0.5...2 x 2.5 mm ² |

| | |
|--|---|
| Positive opening | With |
| Minimum actuation speed | 6 m/min |
| [Ie] rated operational current | 3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A 0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 300 V conforming to CSA C22.2 No 14 contact block 300 V conforming to UL 508 contact block 500 V degree of pollution 3 conforming to IEC 60947-1 contact block |
| Resistance across terminals | 0.25 mOhm conforming to IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1 |
| Short-circuit protection | 10 A by gG cartridge fuse |
| Electrical durability | 5000000 cycles, DC-13 120 V, 4 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 10 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width | 40 mm |
| Height | 77 mm |
| Depth | 44 mm |
| Product weight | 0.31 kg |
| Terminals description ISO n°1 | (11-12)NC (21-22)NC |
| Compatibility code | ZCKJ |

Environment

| | |
|---------------------------------------|---|
| IP degree of protection | IP66 |
| IK degree of protection | IK07 |
| Ambient air temperature for operation | 10...120 °C for high temperature -40...70 °C for low temperature -25...70 °C for standard environment |
| Ambient air temperature for storage | -40...120 °C |
| Environmental characteristic | Low temperature High temperature Standard environment |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0918 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|