



## Main

|                            |   |
|----------------------------|---|
| Range of product           | OsiSense XC   |
| Series name                | Standard format   |
| Product or component type  | Limit switch lever  |
| Device short name          | ZCY   |
| Product compatibility      | XCKD<br>XCKP<br>XCKT  |
| Associated head            | ZCE01<br>ZCE05  |
| Movement of operating head | Rotary  |
| Type of operator           | Roller lever spring return thermoplastic (variable length, roller diameter 50 mm) |
| Tracks                     | No track  |
| Type of approach           | Lateral approach  |

## Complementary

|                     |               |
|---------------------|---------------|
| Switch actuation    | By 30° cam    |
| Positive opening    | With          |
| Device presentation | Basic element |
| Compatibility code  | ZCY           |



## Environment

|                                       |                      |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C          |
| Ambient air temperature for storage   | -40...70 °C          |
| Environmental characteristic          | Standard environment |

## Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 0851 - Schneider Electric declaration of conformity |

 [Schneider Electric declaration of conformity](#)

|                                  |   |
|----------------------------------|---|
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>  |
| Product environmental profile    | Available<br> <a href="#">Product environmental</a>                          |
| Product end of life instructions | Need no specific recycling operations<br> <a href="#">End of life manual</a> |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|