



Main

| | |
|----------------------------|--|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch lever |
| Device short name | ZCY |
| Product compatibility | XCKD XCKP XCKT XCMD |
| Associated head | ZCE09 |
| Movement of operating head | Rotary |
| Type of operator | Stay put forked arm with rollers stay put (2 tracks) |
| Tracks | 21/35 mm for XCMD 25/39 mm for XCKD 25/39 mm for XCKP 25/39 mm for XCKT |
| Type of approach | Lateral approach |

Complementary

| | |
|--------------------|-----------------|
| Switch actuation | By specific cam |
| Positive opening | Without |
| Compatibility code | ZCY |

Environment

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Schneider Electric ZCY61

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1001 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Available |
| Product end of life instructions | Need no specific recycling operations Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|